



KEY FEATURES


- Heavy Duty Thermoplastic Housing
- Compact & Lightweight Design
- Semi-Sealed Pawl Plate Cover
- Side Payout
- Individually Serialised
- External Shock absorbing System
- Top Connection with swivel & Triple Action Carabiner
- Various Bottom Connections available
- Up to 10 years in service
- Custom options for Housing and shock pack cover available

TECHNICAL INFORMATION

- Capacity - 140kg
- Length - 2m
- Max Arresting Force - 6kN
- Webbing - 19mm UHMWPE
- For Overhead and Horizontal usage (360°)

STANDARDS

- EN360:2002
- AS/NZS 1891.3:2020



Product No.	Bottom Connector	Weight	Dimension mm		
			A	B	C
PFLC02CTCT	Triple Action Carabiner	0.9kg	440	75	65
PFLC02CTSHD	Double Action Scaffold	1.0kg	573	75	65
PFLC02CTSHT	Triple Action Scaffold	1.2kg	573	75	65
PFL02CTACTA	Aluminium TAK	0.9kg	452	75	65

ATOMIC Safety Products

Unit 8/7 Cook CT North Lakes QLD 4509

Customer Service:

Email: admin@atomicsafety.com.au

Web: atomicsafety.com.au

CARBON SELF-RETRACTING DEVICE

Individually serialized

360° Swivel top

Semi-sealed pawl plate cover

Side payout

Fall Indicator

Durable thermoplastic housing

External shock absorbing system

Multiple options for connectors

ATOMIC Safety Products

Unit 8/7 Cook CT North Lakes QLD 4509

Customer Service:

Email: admin@atomicsafety.com.au

Web: atomicsafety.com.au